

MP 600 - Technical Specifications



Description

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Telehandler
Industrial: Telehandler • Universal Vehicle

Version	SPECIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	1185
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3530
Rim Rec	13 SDC
Rim Alt	12

Load capacity (Kg)

	km/h / bar	3.50
	40 DW	3650
	50 DW	3550

Printed on 3/25/2023 3:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..