

MULTIMAX MP 515 - Data Sheet



Description

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Universal Vehicle • Fertilizer Truck

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
405/70 R 20 MPT	STANDARD	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	407	1076	493	3286	TL	E4-54R-0016565
425/75 R 20 MPT	STANDARD	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	421	1146	522	3491	TL	E11-54R-0017872
445/65 R 22.5 MPT	STANDARD	160 G	13	14	444	1150	527	3532	TL	E11-54R-0017868

Printed on 3/28/2023 1:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..