

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	340/80 R 20 IND
LI/SS	144 A8/B

Dimensions US Standard

Usa code	94052875
Section Width (inch)	13.5
Overall Diameter (inch)	41.4
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	126.5
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002969

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2970	3530	4010	4570	5130	5500	6170	-	-
25	2970	3530	4010	4570	5130	5500	6170	-	-
20	3170	3770	4300	4890	5490	5890	6610	-	-
15	3300	3910	4460	5080	5700	6110	6860	-	-
5 Cyc.	3620	4450	5240	6020	6860	7460	8430	8900	9260
Static	5540	6820	8020	9240	10520	11430	12930	13630	14200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 12:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..