

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	480/80 R 26 IND
LI/SS	167 A8/B

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1428
Static Loaded Radius (mm)	638
Rolling Circumference (mm)	4287
SRI (mm)	675
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-008146

Load capacity (Kg)

km/h / bar	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
50	2575	2815	3055	3295	3540	3780	4020	4260	4500	4740	4975	5215	5450	-	-
40	2575	2815	3055	3295	3540	3780	4020	4260	4500	4740	4975	5215	5450	-	-
30	2790	3045	3300	3550	3805	4060	4315	4565	4820	5075	5330	5580	5835	-	-
25	2890	3155	3420	3680	3945	4210	4475	4735	5000	5265	5525	5790	6050	-	-
10 Cyc.	3200	3555	3910	4265	4620	4975	5330	5685	6040	6395	6750	7460	8175	-	-
Static	4900	5445	5990	6535	7080	7625	8170	8715	9260	9805	10350	10895	11445	11990	12535

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 5:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..