

MULTIMAX MP 538 - Technical Specifications



Description

MULTIMAX MP 538 is a radial multipurpose tire specifically designed for several applications and machineries: graders and loaders operating in winter conditions, as well as telehandlers, universal vehicles and sweepers in road maintenance.

Thanks to the strong steel-belted casing, MULTIMAX MP 538 allows to carry heavy loads even at high speeds. In addition, its unique tread design helps maintaining excellent traction on ice and snow.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Telehandler • Universal Vehicle
Industrial: Grader • Loader

Version	STEEL BELTED
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	152 G

Dimensions US Standard

Usa code	94069682
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.1
Rolling Circumference (inch)	129.5
Rim Rec	W13

Load capacity (lbs)

mph / psi	87
55	7850
40	8500
25	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..