

# MULTIMAX MP 540 - Technical Specifications



## Description

MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Universal Vehicle

Industrial: Universal Vehicle

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 335/80 R 18<br>(12.5 R 18) |
| LI/SS     | 132 K                      |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94069422        |
| Overall Width (inch)         | 13.4            |
| Overall Diameter (inch)      | 38.8            |
| Static Loaded Radius (inch)  | 17.6            |
| Rolling Circumference (inch) | 118.1           |
| Rim Rec                      | 11              |
| ECE                          | E11-54R-0019559 |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 51   |
| 68        | 4405 |

Printed on 4/14/2024 3:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..