



## MULTIMAX MP 540 - Data Sheet

### Description

MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability



### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Universal Vehicle

Industrial: Universal Vehicle

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>315/55 R 16</b>	STANDARD	94068999	120 K / 124 F	W10L	11	12	29.6	13.9	91.5	TL	E11-54R-0019558
<b>335/80 R 18 (12.5 R 18)</b>	STANDARD	94069422	132 K			13.4	38.8	17.6	118.1	TL	E11-54R-0019559
<b>275/80 R 20 (10.5 R 20)</b>	STANDARD	94071357	134 K	W9	9	10.6	37.6	17.4	114.7	TL	E11-54R-0020628
<b>335/80 R 20</b>	STANDARD	94033539	149 K	11	-	13.4	41.1	19.4	128.3	TL	E11-54R-0015909
<b>365/80 R 20 (14.5 R 20)</b>	STANDARD	94069873	152 K	11		14.4	42.8	19.5	130.2	TL	E11-54R-0020145
<b>405/70 R 20 (16.0/70 R 20)</b>	STANDARD	94072903	152 K	13	12; 13 SDC	15.8	42.6	19.3	129.7	TL	
<b>405/70 R 24 (16.0/70 R 24)</b>	STANDARD	94074600	152 J	13		15.8	46.2	20.9	141.2	TL	E11-54R-0020862

Printed on 4/15/2024 11:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..