

# PORTMAX PM 90 - Technical Specifications



## Description

PORTMAX PM 90 has been specially designed for reach stackers in several applications including industrial handling and steelworks. It is an All Steel radial tire that provides great durability and stability. Its special antistatic tread compound ensures particular heat resistance and an extended tire life-cycle. PORTMAX PM 90 offers reduced rolling resistance improving fuel economy.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Industrial: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

## Dimensions International Standard

Overall Width (mm)	485
Overall Diameter (mm)	1845
Static Loaded Radius (mm)	857
Rolling Circumference (mm)	5624
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

## Load capacity (Kg)

km/h / bar	10.00
25	21200

Printed on 4/23/2024 1:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..