

POWER TRAX HD - Data Sheet



Description

POWER TRAX HD premium tire is specially designed for equipment in port and underground mining applications. Its deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces. The specially designed rim guard ensures protection against flats and wheel damage in the rim flange area.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Container Handler

OTR: Underground Mining Vehicle

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	Tread Depth	ECE
12.00 - 20	IMPLEMENT	94055944	172 A8	20	8.50	9.0	12.6	45.3	TT	43	E11-106R-003422
12.00 - 20	IMPLEMENT	94055951	173 A8	28	8.50	9.0	12.6	45.3	TT	43	E11-106R-003348
12.00 - 20	STANDARD	94007660		20	8.50	9.0	12.6	45.3	TT	43	
12.00 - 20	STANDARD	94007684		28	8.50	9.0	12.6	45.3	TT	43	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..