

# **POWERTRAILER SR 331 - Data Sheet**



### Description

POWERTRAILER SR 331 is BKT's brand-new All Steel radial tire specifically designed for trailers and tankers in transport applications. Engineered for both field and road usage, POWERTRAILER SR 331 distinguishes itself with good flotation properties in the fields as well as excellent traction on asphalt or other hard, improved surfaces. The All Steel construction stands for high load capacity, extraordinary casing stability, and an extended tire life. The special sidewall rib provides exceptional protection against impacts and the effects of tire rubbing, while the hexagonal bead with chafer reinforcement makes sure that the tire perfectly fits on the rim. In addition, the multi-block tread pattern ensures reduced rolling resistance, a uniform contact pressure, and smooth roadability. Thanks to all these features, POWERTRAILER SR 331 is synonym for fuel economy and road comfort.

#### **UM**

**US Standard** 

#### Construction



## Machinery

Agriculture: Tanker • Trailer

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре	ECE
560/60 R 22.5	IMPLEMENT	94075997	169 D	AG 16.00	17.00 ; AG18.00	21.9	49	22.2	148.6	TL	E11-106R-0010147
560/60 R 22.5	IMPLEMENT	94073962	165 D	AG 16.00	17.00 : AG18.00	21.9	49	22.2	148.6	TL	E11-106R-0010087

#### Printed on 4/27/2024 10:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..