

# RIDEMAX FL 615 - Technical Specifications



## Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Spreader • Tanker • Trailer

|                    |              |
|--------------------|--------------|
| Version            | STEEL BELTED |
| Type               | TL           |
| Tyre Size          | 800/65 R 32  |
| LI/SS              | 185 D        |
| LI/SS DRIVE WHEEL  | 185 D        |
| LI/SS FREE ROLLING | 185 D        |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 830             |
| Overall Diameter (mm)      | 1853            |
| Static Loaded Radius (mm)  | 834             |
| Rolling Circumference (mm) | 5624            |
| SRI (mm)                   | 875             |
| Rim Rec                    | DW 27 B         |
| ECE                        | E11-106R-007528 |

## Load capacity (Kg)

| km/h / bar | 1.0  | 1.2  | 1.6  | 2.0   | 2.4   | 2.8   | 3.2   | 3.6   |
|------------|------|------|------|-------|-------|-------|-------|-------|
| 65         | 3980 | 4350 | 5275 | 5830  | 6755  | 7680  | 8420  | 9250  |
| 50         | 4815 | 5265 | 6385 | 7055  | 8175  | 9295  | 10190 | 11195 |
| 40         | 5410 | 5915 | 7175 | 7930  | 9185  | 10445 | 11450 | 12580 |
| 30         | 6010 | 6570 | 7965 | 8805  | 10200 | 11600 | 12715 | 13970 |
| 25         | 6285 | 6870 | 8335 | 9210  | 10670 | 12135 | 13300 | 14615 |
| 10         | 7160 | 7830 | 9495 | 10490 | 12155 | 13820 | 15155 | 16650 |

Printed on 4/18/2024 3:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..