

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	162 D

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1180
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3614
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006972

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
70	1645	1990	2205	2555	2900	3200	3505	3850	4110	4325
65	1805	2185	2425	2805	3185	3515	3850	4230	4515	5750
50	2185	2645	2935	3395	3855	4255	4660	5120	5465	5750
40	2455	2975	3295	3815	4330	4785	5235	5750	6140	6460
25	2855	3455	3830	4430	5030	5555	6080	6680	7130	7505
10	3250	3935	4365	5045	5730	6330	6930	7610	8125	8550

Printed on 4/20/2024 3:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..