

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D/162 E

Dimensions US Standard

Usa code	94045891
Section Width (inch)	21.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	148.3
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E4-106R-001403

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73
45	3430	3850	4780	5430	6280	7120	7780	8530	9370	10470
40	3730	4190	5200	5920	6830	7750	8470	9280	10200	11350
30	4520	5070	6300	7160	8280	9390	10250	11240	12350	13750
25	5070	5690	7080	8050	9290	10550	11520	12620	13870	15440
15	5890	6610	8220	9350	10800	12260	13380	14670	16110	17940
5	6700	7530	9370	10650	12300	13950	15230	16710	18350	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..