

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	173 D

Dimensions International Standard

Section Width (mm)	605
Overall Diameter (mm)	1495
Static Loaded Radius (mm)	681
Rolling Circumference (mm)	4495
SRI (mm)	725
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-007198

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.5	5
70	2045	2250	2725	3020	3490	3965	4380	4795	5265	5620	5915
65	2245	2470	2990	3315	3835	4355	4810	5265	5785	6175	6500
50	2715	2990	3620	4015	4645	5270	5825	6375	7000	7475	7865
40	3050	3360	4070	4510	5220	5925	6545	7165	7870	8400	8840
30	3390	3730	4515	5010	5795	6580	7265	7955	8740	9325	9815
25	3545	3905	4725	5240	6060	6885	7600	8320	9145	9760	10270
10	4040	4450	5385	5970	6905	7840	8660	9480	10415	11115	11700

Printed on 4/2/2023 11:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..