

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 360/80 R 20 IND |
| LI/SS | 143D/147A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------------|
| Usa code | 94071074 |
| Section Width (inch) | 14.1 |
| Overall Diameter (inch) | 42.7 |
| Static Loaded Radius (inch) | 19.2 |
| Rolling Circumference (inch) | 127.4 |
| Rim Rec | 11 |
| Rim Alt | W 10 ; W 11 ; 12 ; W 12 |
| ECE | E11-106R-007845 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2890 | 3490 | 4160 | 4630 | 4810 | 4990 | 5470 | 6010 |
| 30 | 3120 | 3770 | 4490 | 5000 | 5200 | 5390 | 5910 | 6490 |
| 25 | 3260 | 3940 | 4680 | 5220 | 5420 | 5630 | 6170 | 6780 |
| 20 | 3460 | 4190 | 4980 | 5560 | 5780 | 5990 | 6570 | 7210 |

Printed on 4/18/2024 9:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..