



ROCK GRIP E4 - Data Sheet



Description

ROCK GRIP (E-4) is a bias-ply tire specially designed for haul trucks in mining service and quarry operations. Whenever your short-haul site conditions require both heat resistance and cut protection, ROCK GRIP is the tire you can rely upon.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 - 25	STANDARD	E4	32	10.00/2.0		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	24	10.00/2.0		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	28	10.00/1.5		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	28	10.00/1.5		375	1410	649	4173	TT	50
14.00 - 25	STANDARD	E4	28	10.00/2.0		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	28	10.00/2.0		375	1410	649	4173	TT	50
14.00 - 25	STANDARD	E4	32	10.00/1.5		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	24	10.00/1.5		375	1410	649	4173	TL	50
14.00 - 25	STANDARD	E4	24	10.00/2.0		375	1410	649	4173	TT	50
14.00 - 25	STANDARD	E4	24	10.00/1.5		375	1410	649	4173	TT	50
16.00 - 25	STANDARD	E4	32	11.25/2.0	13.00/2.0	470	1525	699	4514	TL	52
16.00 - 25	STANDARD	E4	28	11.25/2.0	13.00/2.0	470	1525	699	4514	TL	52
16.00 - 25	STEEL BELTED	E4	32	11.25/2.0	13.00/2.0	470	1525	699	4514	TL	52
18.00 - 25	CUT RESISTANT	E4	40	13.00/2.5	15.00/2.5	510	1650	753	4885	TT	54
18.00 - 25	STANDARD	E4	40	13.00/2.5	15.00/2.5	510	1650	753	4885	TL	54
18.00 - 25	STANDARD	E4	32	13.00/2.5	15.00/2.5	510	1650	753	4885	TL	54
18.00 - 25	STANDARD	E4	36	13.00/2.5	15.00/2.5	510	1650	753	4885	TL	54
18.00 - 25	STANDARD	E4	40	13.00/2.5	15.00/2.5	510	1650	753	4885	TT	54
18.00 - 25	STANDARD	E4	24	13.00/2.5	15.00/2.5	510	1650	753	4885	TT	54
18.00 - 25	STANDARD	E4	32	13.00/2.5	15.00/2.5	510	1650	753	4885	TT	54
18.00 - 33	CUT RESISTANT COMPOUND	E4	40	13.00/2.5		510	1887	869	5586	TL	60
18.00 - 33	CUT RESISTANT COMPOUND	E4	36	13.00/2.5		510	1887	869	5586	TL	60
18.00 - 33	STANDARD	E4	36	13.00/2.5		510	1887	869	5586	TT	60
18.00 - 33	STANDARD	E4	36	13.00/2.5		510	1887	869	5586	TL	60
18.00 - 33	STANDARD	E4	40	13.00/2.5		510	1887	869	5586	TT	60
18.00 - 33	STANDARD	E4	40	13.00/2.5		510	1887	869	5586	TL	60
18.00 - 33	STANDARD	E4	44	13.00/2.5		510	1887	869	5586	TL	60
21.00 - 35	CUT RESISTANT COMPOUND	E4	40	15.00/3.0		580	2040	943	6068	TL	60
21.00 - 35	CUT RESISTANT COMPOUND	E4	36	15.00/3.0		580	2040	943	6068	TL	60
21.00 - 35	STANDARD	E4	36	15.00/3.0		580	2040	943	6068	TL	60
21.00 - 35	STANDARD	E4	40	15.00/3.0		580	2040	943	6068	TL	60
24.00 - 35	CUT RESISTANT COMPOUND	E4	48	17.00/3.5		655	2190	1003	6482	TL	62
24.00 - 35	STANDARD	E4	48	17.00/3.5		655	2190	1003	6482	TL	62
24.00 - 49	CUT RESISTANT COMPOUND	E4	48	17.00/3.5		655	2531	1184	7498	TL	62
24.00 - 49	STANDARD	E4	42	17.00/3.5		655	2531	1184	7498	TL	62
24.00 - 49	STANDARD	E4	48	17.00/3.5		655	2531	1184	7498	TL	62
27.00 - 49	CUT RESISTANT COMPOUND	E4	54	19.50/4.0		740	2695	1253	7985	TL	68
27.00 - 49	CUT RESISTANT COMPOUND	E4	48	19.50/4.0		740	2695	1253	7985	TL	68
27.00 - 49	STANDARD	E4	54	19.50/4.0		740	2695	1253	7985	TL	68
27.00 - 49	STANDARD	E4	48	19.50/4.0		740	2695	1253	7985	TL	68
30.00 - 51	CUT RESISTANT COMPOUND	E4	52	22.00/4.5		830	2910	1350	8615	TL	72
30.00 - 51	STANDARD	E4	46	22.00/4.5		830	2910	1350	8615	TL	72
30.00 - 51	STANDARD	E4	52	22.00/4.5		830	2910	1350	8615	TL	72

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/17/2025 12:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..