

# **ROCK GRIP (T) - Technical Specifications**



## Description

ROCK GRIP (E-4) best suits on/off trucks in quarries and short-haul mining applications to carry heavy loads. The special tread compound minimizes cuts and punctures on roughest ground conditions. ROCK GRIP (E-4) offers exceptional traction and an extended tire life-cycle.

### UM

**US Standard** 

## Construction

BIAS

# Machinery

OTR: On/Off Truck • Rigid Dump Truck

| Version   | STANDARD   |
|-----------|------------|
| Туре      | тт         |
| Tyre Size | 10.00 - 20 |

# **Dimensions US Standard**

| Usa code                | 94050802 |
|-------------------------|----------|
| Ply Rating              | 18       |
| Overall Width (inch)    | 11       |
| Overall Diameter (inch) | 42.9     |
| Rim Rec                 | 7.5      |
| Rim Alt                 | 7.0      |

# Load capacity (lbs)

| mph / psi | 110  |
|-----------|------|
| 55 LS/LD  | 6170 |

### Printed on 4/27/2024 12:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..