

RT 857 - Technical Specifications



Description

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

UM

US Standard

Construction



Machinery

Agriculture: Tractor

Version	STANDARD
Туре	TL
Tyre Size	380/85 R 24 (14.9 R 24)
LI/SS	131 A8/B

Dimensions US Standard

Usa code	94053773
Section Width (inch)	15
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	22.3
Rolling Circumference (inch)	148.9
Rim Rec	W 12
Rim Alt	W 13; W 11
ECE	E11-106R-002977
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2370	2760	3140	3530	3910	4300
25	2370	2760	3140	3530	3910	4300
20	2540	2950	3370	3780	4200	4610
5 LT	3170	3690	4210	4730	5250	5760
5 HT	2540	2950	3370	3780	4200	4610

Printed on 4/19/2024 11:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..