

## SAND STAR - Technical Specifications



### Description

SAND STAR is a block pattern tire specially designed for trailers. It provides excellent traction on sandy surfaces and best ground contact. It also reduces soil compaction.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	9.00 - 13
LI/SS	116 A8

# Dimensions International Standard

Ply Rating	8
Section Width (mm)	245
Overall Diameter (mm)	784
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005261

## Load capacity (Kg)

km/h / bar	2.75
40 FR LLV	1250

Printed on 4/20/2024 4:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..