

SAND STAR - Technical Specifications



Description

SAND STAR is a block pattern tire specially designed for trailers. It provides excellent traction on sandy surfaces and best ground contact. It also reduces soil compaction.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	9.00 - 13
LI/SS	119 A8

Dimensions US Standard

Usa code	94031733
Ply Rating	10
Section Width (inch)	9.6
Overall Diameter (inch)	30.9
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005263

Load capacity (lbs)

mph / psi	48
25 FR LLV	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 5:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..