



SM 54 L4S - Data Sheet

Description

SM 54 (L-4S) has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. It features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance to ensure an extended tire life-cycle. *The picture in the gallery below refers to size 18.00-25 only.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.00 - 25	INDUSTRIAL	94015610	L4S	28	11.25/2.0	13.00/2.0	16.9	57.9	26.6	171.4	TL
16.00 - 25	INDUSTRIAL	94015627	L4S	32	11.25/2.0	13.00/2.0	16.9	57.9	26.6	171.4	TL
18.00 - 33	PORT INDUSTRIAL	94050208	L4S	36	13.00/2.5		21.1	74.6	33.1	220.8	TL
18.00 - 33	PORT INDUSTRIAL	94050215	L4S	40	13.00/2.5		21.1	74.6	33.1	220.8	TL

Printed on 9/26/2023 6:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..