



SM 55 IND-5S - Data Sheet

Description

SM 55 IND-5S has been specially designed for reach stackers and container handlers. Its special abrasion-resistant tread compound provides an extended tire life on asphalt or concrete surfaces and offers excellent stability to vehicles in lift mode.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Container Handler

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	PORT INDUSTRIAL	94060498	IND5	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	12.2	50.2	23.4	148.7	TT
18.00 - 25	PORT SPECIAL	94039609	IND5	40	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..