

## SM 55 L5S - Technical Specifications



### Description

SM 55 (L-5S) is a bias-ply tire ideal for underground mining operations. The specially designed cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The extra-deep L-5 S tread depth guarantees an extended tire life. The tire is also available in a steel-belted version.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Low Profile Dump Truck (LPDT) • Underground Mining Vehicle

Version	STEEL BELTED
Type	TL
Tyre Size	26.5 - 25

Dimensions US Standard

Usa code	94039951
Ply Rating	28
Overall Width (inch)	27.6
Overall Diameter (inch)	70.8
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	209.5
Rim Rec	22.00/3.0
TRA Code	L5S
Tread Depth	121

Load capacity (lbs)

mph / psi	69
5	34200
10	29700
15	27300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 4:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..