SM 55 L5S - Technical Specifications

Description

SM 55 (L-5S) is a bias-ply tire ideal for underground mining operations. The specially designed cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The extra-deep L-5 S tread depth guarantees an extended tire life. The tire is also available in a steel-belted version.

UM

International Standard

Construction

BIAS

Machinery

OTR: Low Profile Dump Truck (LPDT) • Underground Mining Vehicle

Version	STEEL BELTED
Type	TL
Tyre Size	26.5 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	700
Overall Diameter (mm)	1798
Static Loaded Radius (mm)	816
Rolling Circumference (mm)	5322
Rim Rec	22.00/3.0
TRA Code	L5S

Load capacity (Kg)

km/h / bar	5.50
10	17000
15	14790
25	13600

Printed on 4/20/2024 3:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..