

SNOW GRIP - Technical Specifications



Description

SNOW GRIP is specifically engineered for forklifts operating in low-temperature environments. The unique tread design features multiple gripping edges for superior grip on fresh or compact snow, resulting in excellent cornering and braking performance on icy and snowy surfaces. The dual bead construction along with the strong casing and reinforced sidewall provides higher load capacity, excellent stability and handling in lift mode in addition to a long tire life.

UM

International Standard

Construction



Machinery

Industrial: Forklift

Version	STANDARD
Туре	π
Tyre Size	7.50 - 16
II/SS	131 Δ2

Dimensions International Standard

Ply Rating	12
Section Width (mm)	210
Overall Diameter (mm)	810
Rim Rec	6.0

Load capacity (Kg)

km/h / bar	5.0
10	1950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..