

SNOW - RIDE (A) - Technical Specifications



Description

SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Compact Loader

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	15.5/60 - 18

Dimensions US Standard

Usa code	94041398
Ply Rating	10
TMPH	1
Section Width (inch)	15.6
Overall Diameter (inch)	36.9
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	110.8
Rim Rec	W 13
ECE	'E11-106R-005302

Load capacity (lbs)

mph / psi	38
5	5290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 1:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..