

SNOW - RIDE (B) - Technical Specifications

Description

SNOW-RIDE is particularly suitable for road applications in winter conditions with skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Dozer • Loader



Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

Dimensions US Standard

Usa code	94054138
Ply Rating	16
Section Width (inch)	17.5
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	159.2
Rim Rec	14.00/1.5
TRA Code	L2

Load capacity (lbs)

mph / psi	69
5	16100

Printed on 4/24/2024 10:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..