# SNOW - RIDE (B) - Technical Specifications

## Description

SNOW-RIDE is particularly suitable for road applications in winter conditions with skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

## UM

US Standard

## Construction

BIAS

## Machinery

Industrial: Dozer • Loader

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TL |
| **Tyre Size** | 17.5 - 25 |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94054138 |
| **Ply Rating** | 16 |
| **Section Width (inch)** | 17.5 |
| **Overall Diameter (inch)** | 53.1 |
| **Static Loaded Radius (inch)** | 23.9 |
| **Rolling Circumference (inch)** | 159.2 |
| **Rim Rec** | 14.00/1.5 |
| **TRA Code** | L2 |

## Load capacity (lbs)

| mph / psi | 69 |
|---|---|
| 5 | 16100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..