

SR 713 - Technical Specifications



Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	VF 445/65 R 22.5
LI/SS	176 D

Dimensions US Standard

Usa code	94068944
Overall Width (inch)	17.3
Overall Diameter (inch)	45.7
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	138.4
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-106R-006976
TRA Code	I1

Load capacity (lbs)

mph / psi	78
40	15700

Printed on 12/5/2023 3:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..