



SR 713 - Data Sheet



Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
VF 245/70 R 19.5	STANDARD	94067732	I1	142 D	7.50		9.6	33.2	14.7	100.7	TL	E11-106R-006978
VF 265/70 R 19.5	STANDARD	94070305	I1	146 D	7.50	8.25	10	34.4	15.4	102.8	TL	E11-106R-007581
VF 255/70 R 22.5	STANDARD	94067329	I1	149 D	8.25	7.50	10	36.7	16	109.8	TL	E11-106R-006860
VF 295/75 R 22.5	STANDARD	94057832	I1	151 D	9.00	8.25	11	40.2	17.7	119.8	TL	E11-106R-005500
VF 295/75 R 22.5	STANDARD	94068920	I1	155 D	9.00	8.25	11	40.2	17.7	119.8	TL	E11-106R-006977
VF 385/65 R 22.5	STANDARD	94071364	I1	163 D	11.75	12.25	15.2	42.5	19.2	128	TL	E11-106R-007881
VF 445/65 R 22.5	STANDARD	94059416	I1	169 D	13.00	14.00	17.3	45.7	21	138.4	TL	E11-106R-005501
VF 445/65 R 22.5	STANDARD	94068944	I1	176 D	13.00	14.00	17.3	45.7	21	138.4	TL	E11-106R-006976

Printed on 4/23/2024 6:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..