

## STEER FARM - Technical Specifications



### Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	170
Overall Diameter (mm)	740
Static Loaded Radius (mm)	353
Rolling Circumference (mm)	2279
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F
ECE	E4-106R-002186
TRA Code	F2

## Load capacity (Kg)

km/h / bar	4.50
30	670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 4:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..