

## STEER GRIP - Technical Specifications



### Description

STEER GRIP is the perfect steering-axle fitment for on/off trucks. The wide central rib with straight lugs makes the tire suitable for free rolling applications and provides enhanced grip for excellent performance on both wet and dry conditions off the road. The special tread compound has been designed for combining best wear resistance with cut-and-chip resistance whereas the strong casing ensures an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: On/Off Truck

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

## Dimensions International Standard

Ply Rating	18
Overall Width (mm)	286
Overall Diameter (mm)	1085
Static Loaded Radius (mm)	510
Rolling Circumference (mm)	3290
Rim Rec	7.5
Rim Alt	7.0

## Load capacity (Kg)

km/h / bar	7.6
90 LS/LD	2800

Printed on 4/13/2024 11:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..