

SUPER GRADER - Data Sheet



Description

SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Grader

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
13.00 - 24	STANDARD	G2	12	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	340	1275	588	3800	TT	25
13.00 - 24	STANDARD	G2	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	340	1275	588	3800	TT	25
13.00 - 24	STANDARD	G2	12	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	340	1275	588	3800	TL	25
13.00 - 24	STANDARD	G2	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	340	1275	588	3800	TL	25
14.00 - 24	STANDARD	G2	12	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC	364	1335	598	3952	TT	25
14.00 - 24	STANDARD	G2	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	364	1335	598	3952	TT	25
14.00 - 24	STANDARD	G2	12	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC	364	1335	598	3952	TL	25
14.00 - 24	STANDARD	G2	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	364	1335	598	3952	TL	25
16.00 - 24	STANDARD	G2	16	10.00 VA SDC		430	1450	644	4307	TL	30

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..