

SUPER TRAX HD - Technical Specifications



Description

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

Dimensions International Standard

Ply Rating	14
Section Width (mm)	200
Overall Diameter (mm)	692
Static Loaded Radius (mm)	323
Rolling Circumference (mm)	2088
Rim Rec	5.00 S

Load capacity (Kg)

km/h / bar	9.00
25 LOAD WHEEL	2755
25 STEER WHEEL	2120
10 OTHER VEHICLES	2755
25 OTHER VEHICLES	2120
STATIC SIDE LOADER	3200

Printed on 4/25/2024 9:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..