

SUPER TRAX HD - Data Sheet



Description

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

UM

International Standard

Construction

✚ BIAS

Machinery

Industrial: Forklift

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
6.00 - 9	STANDARD	12	4.00 E		168	548	256	1672	TT
6.50 - 10	STANDARD	12	5.00 F	5.50 F	195	600	282	1838	TT
7.00 - 12	STANDARD	14	5.00 S		200	692	323	2088	TT
8.15 - 15 (28 X 9 - 15)	STANDARD	14	7.00	7 BD	220	715	332	2169	TT
8.25 - 15	STANDARD	16	6.50	7.0	245	845	395	2434	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..