

SURE TRAX HD - Technical Specifications

Description

SURE TRAX HD is a block pattern tire for skid steers in construction applications. It shows excellent cut and chip resistance as well as top rim protection. SURE TRAX HD is ideal for paved surfaces and heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer



Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	12
Section Width (mm)	325
Overall Diameter (mm)	855
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2522
Rim Rec	9.75

Load capacity (Kg)

km/h / bar	5.50
10	2865
15	2265
25	2090

Printed on 3/28/2023 2:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..