

## TF 8181 - Technical Specifications



### Description

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor  
Industrial: Trailer

Version	SPECIAL
Type	TT
Tyre Size	7.50 - 20
LI/SS	109 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	915
Static Loaded Radius (mm)	431
Rolling Circumference (mm)	2725
Rim Rec	5.50 F
Rim Alt	5.00 F
ECE	E11-106R-005255
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.40
30	1030

Printed on 4/15/2024 2:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..