

# **TF 9090 - Technical Specifications**



# **Description**

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

#### **UM**

International Standard

#### Construction



# Machinery

Agriculture: Small Tractor

Industrial: Trailer

Version	STANDARD
Туре	ТТ
Tyre Size	11.00 - 16
LI/SS	118 A6

### **Dimensions International Standard**

Ply Rating	8
Section Width (mm)	320
Overall Diameter (mm)	970
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2890
Rim Rec	W 10 L
Rim Alt	W8;W8L
ECE	E4-106R-002673
TRA Code	F2

# Load capacity (Kg)

km/h / bar	2.50
30	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/1/2025 10:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..