

TF 9090 - Technical Specifications



Description

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor
Industrial: Trailer

Version	SPECIAL
Type	TT
Tyre Size	7.50 - 18
LI/SS	101 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	207
Overall Diameter (mm)	860
Static Loaded Radius (mm)	404
Rolling Circumference (mm)	2562
Rim Rec	5.50 F
TRA Code	F2

Load capacity (Kg)

km/h / bar	2.80
30	825

Printed on 4/20/2024 5:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..