



TR 128 - Data Sheet



Description

TR 128 has been specially designed for utility tractors and rototillers. The wide and deep lug design and the special cut-and-chip resistance compound provide an extended tire service life. TR 128 features maximum traction on wet soil.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Rototiller • Universal Vehicle

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
180/85 D 12	STANDARD	94058129	63 A6	4	5 JA		6.5	24.1	11.6	72.7	TT	E11-106R-004821
180/85 D 12	STANDARD	94059256	72 A8	6	5 JA		6.5	24.1	11.3	72.7	TT	E11-106R-005207
5 - 12	STANDARD	94044887		4	4 JA		5	21.8	10.3	66.9	TT	E11-106R-003477
5 - 12	STANDARD	94055883	60 A8	6	4 JA		5	21.8	10.3	66.9	TT	E11-106R-005189
6.00 - 12	STANDARD	94044894	65 A8	4	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	E11-106R-003478
6.00 - 12	STANDARD	94045242	72 A8	6	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	E11-106R-003479
6.00 - 12	STANDARD	94060511	78 A8	8	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	
7 - 14	STANDARD	94050345	92 A8	8	5 JA	5 J	6.8	27.2	12.7	82.1	TT	E11-106R-004093

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 2:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..