TR 137 - Technical Specifications

Description

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the “aramid-belted” version provides better puncture resistance and protection against all typical damages of this application; the “HD” version provides extraordinary cut and chip resistance, and an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Harvester

Version	STANDARD
Type	TL
Tyre Size	30.5L - 32
LI/SS	164 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	770
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	831
Rolling Circumference (mm)	5520
Rim Rec	DH 27 B
Rim Alt	DW 27 B
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.60
30	5000

Printed on 5/8/2024 4:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..