



## TR 137 - Data Sheet

### Description

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.



### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24.5 - 32	STANDARD	94004317	R1	156 A8	12	DW 21 B	DW 20 B	24.5	71.1	31.8	210.4	TL	E4-106R-002271
24.5 - 32	STANDARD	94004324	R1	159 A8	14	DW 21 B	DW 20 B	24.5	71.1	31.8	210.4	TL	E4-106R-002273
30.5L - 32	ARAMID BELTED	94002986	R1	167 A8	18	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	TL	E4-106R-002271
30.5L - 32	HD	94004355	R1	167 A8	18	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	TL	E4-106R-002283
30.5L - 32	STANDARD	94004331	R1	158 A8	12	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	TL	E4-106R-002274
30.5L - 32	STANDARD	94039913	R1	160 A8	14	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	TL	
30.5L - 32	STANDARD	94004348	R1	164 A8	16	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	TL	E4-106R-002282

Printed on 3/25/2023 3:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..