



## TR 144 - Data Sheet



### Description

TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Small Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
7 - 16	STANDARD	94004706	R1	71 A8	4	6 L ; 6 LB ; 6.00 F		7.2	29.1	13.5	87.5	TT	0	E4-106R-002205
7 - 16	STANDARD	94053537	R1	75 A6	4	6 L ; 6 LB ; 6.00 F		7.2	29.1	13.5	87.5	TL	0	E4-106R-002205
7 - 16	STANDARD	94052202	R1	80 A8	6	6 L ; 6 LB ; 6.00 F		7.2	29.1	13.7	88.7	TT	0	E11-106R-004322
8 - 16	HD	94048373	R1	88 A8	6	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TT	1	E11-106R-004087
8 - 16	SPECIAL	94032006	R1	88 A8	6	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TT	0	E11-106R-004324
8 - 16	STANDARD	94036301	R1	79 A8	4	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TT	0	E11-106R-004323
8 - 16	STANDARD	94004720	R1	88 A8	6	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TT	0	E11-106R-003483
8 - 16	STANDARD	94053544	R1	88 A8	6	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TL	0	E11-106R-003483
8 - 16	STANDARD	94052646	R1	94 A8	8	6 L ; 6 LB ; 6.00 F		7.9	30.9	14.1	92.2	TT	0	E11-106R-004325
9.5 - 16	STANDARD	94041374	R1	92 A8	6	W 8 L	8 LB	9.6	33.5	15.3	100.7	TT	0	E4-106R-002643
9.5 - 16	STANDARD	94042425	R1	99 A8	8	W 8 L	8 LB	9.6	33.5	15.3	100.7	TT	0	E11-106R-004327
9.5 - 16	STANDARD	94053551	R1	92 A8	6	W 8 L	8 LB	9.6	33.5	15.3	100.7	TL	0	E4-106R-002643
9.5 - 16	STANDARD	94053568	R1	99 A8	8	W 8 L	8 LB	9.6	33.5	15.3	100.7	TL	0	E11-106R-004327
8 - 18	SPECIAL	94032013	R1	90 A8	6	W 6	W 7 ; 5.50 F	7.7	32.9	15.4	99.8	TT	0	E11-106R-003496
8 - 18	SPECIAL	94054411	R1	96 A8	8	W 6	W 7 ; 5.50 F	7.7	32.9	15.4	99.8	TT	0	E11-106R-006166
8 - 18	STANDARD	94038909	R1	81 A8	4	W 6	W 7 ; 5.50 F	7.7	32.9	15.2	98.8	TT	0	E11-106R-004328
8 - 18	STANDARD	94004737	R1	90 A8	6	W 6	W 7 ; 5.50 F	7.7	32.9	15.2	98.8	TT	0	E11-106R-006467
8 - 18	STANDARD	94053599	R1	96 A8	8	W 6	W 7 ; 5.50 F	7.7	32.9	15.2	98.8	TT	0	E11-106R-006166
8.3 - 20	HD	94044030	R1	92 A8	6	W 7	W 6	8.3	35	16.3	105.1	TT	1	E11-106R-004101
8.3 - 20	STANDARD	94004713	R1	92 A8	6	W 7	W 6	8.3	35	16.3	105.1	TT	0	E11-106R-003484
9.5 - 22	STANDARD	94004744	R1	100 A8	6	W 8	W 7	9.3	39.4	18.3	118.4	TT	0	E11-106R-003485

Printed on 4/22/2024 5:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..