

TR 145 - Technical Specifications



Description

TR 145 has been specifically designed for small tractors. The special tread pattern provides excellent traction and outstanding self-cleaning properties. The wide and deep lug design ensures an extended tire service life. The TR 145 tire has a large contact area which offers excellent driving comfort and high directional stability.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 160/90 - 12 |
| LI/SS | 72 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94062744 |
| Ply Rating | 6 |
| Section Width (inch) | 6.3 |
| Overall Diameter (inch) | 24.8 |
| Static Loaded Radius (inch) | 11.6 |
| Rolling Circumference (inch) | 77.5 |
| Rim Rec | 4.00 |
| ECE | E11-106R-005854 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|-----|
| mph / psi | 36 |
| 2 | 785 |

Printed on 4/26/2024 10:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..