

TR 173 - Technical Specifications



Description

TR 173 is a tractor tire suitable for wet conditions and paddy fields. The special tread pattern provides outstanding self-cleaning properties in addition to reduced soil compaction thanks to a large contact area.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	9.5 - 24
LI/SS	102 A8

Dimensions US Standard

Usa code	94066988
Ply Rating	6
Section Width (inch)	9.5
Overall Diameter (inch)	41.2
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	127.5
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-006486
TRA Code	R1W

Load capacity (lbs)

mph / psi	30
25	1870

Printed on 4/19/2024 12:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..