

TR 319 - Technical Specifications



Description

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Orchard Harvester • Trencher

Version	STANDARD
Type	TL
Tyre Size	29 X 12.50 - 15
LI/SS	106 B

Dimensions International Standard

Ply Rating	8
Section Width (mm)	312
Overall Diameter (mm)	755
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2264
Rim Rec	10 LB
ECE	E11-106R-004605

Load capacity (Kg)

km/h / bar	3.10
50	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/9/2024 11:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..