



## TR 319 - Data Sheet

### Description

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Orchard Harvester • Trencher



SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>26 X 12.00 - 12</b>	STANDARD	94043637	116 A3	8	10.50 AT	8.0 AT ; 8.5 AT ; 9.0 AT	12.5	25.2	11.4	75.1	TL	E11-106R-003560
<b>29 X 12.50 - 15</b>	STANDARD	94051601	98 B	6	10 LB		12.3	29.7	14.2	89.1	TL	E11-106R-004604
<b>29 X 12.50 - 15</b>	STANDARD	94053247	106 B	8	10 LB		12.3	29.7	14.2	89.1	TL	E11-106R-004605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 9:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..