

TR 390 IND - Technical Specifications



Description

TR 390 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Compactor • Industrial Tractor • Trailer

Version	DUAL BEAD HD
Type	TL
Tyre Size	28L - 26
LI/SS	172 A6

Dimensions International Standard

Ply Rating	20
Section Width (mm)	714
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4545
Rim Rec	DW 25 B
Rim Alt	DW 23 B
TRA Code	R3

Load capacity (Kg)

km/h / bar	2.80
30	6300

Printed on 4/26/2024 7:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..