

## TR 675 - Data Sheet



### Description

TR 675 is a bias tire specially designed for forestry applications. Its robust lug design provides excellent traction and self-cleaning, while the strong casing structure allows to carry heavy loads and its steel belts protect the tire from punctures and damages.

TR 675 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Forwarder

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	LS2	155 A8/161 A2	16	W 16 L	W 18 L	530	1425	663	4440	TL	E11-106R-005271

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..