



TR 678 - Data Sheet



Description

TR 678 has been specially designed for forestry applications. Its robust lug design provides excellent traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

Industrial: Excavator • Trailer

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/55 - 26.5	STEEL BELTED	94074112	LS2	172 A2 / 165 A8	20	AG 20.00		23.8	53.1	0	0	TL	E11-106R-008132
780/50 - 28.5	STEEL BELTED	94068982	LS2	190 A2/ 182 A8	24	AG 26.00		30.3	59.6	0	0	TL	E11-106R-006975
600/65 - 34	STEEL BELTED	94043378	LS2	166 A2 / 162 A6	16	DW 20 B		24	64.7	29.8	193.5	TL	
600/65 - 34	STEEL BELTED	94043385	LS2	170 A2 / 166 A6	20	DW 20 B		24	64.7	29.8	193.5	TL	
600/65 - 34	STEEL BELTED	94032679	LS2	164 A2/160 A6	14	DW 20 B		24	64.7	29.8	193.5	TL	E11-106R-003648
710/55 - 34	STEEL BELTED	94069026	LS2	173 A2/ 168 A6	20	DW 24 B		27.6	64.6	29.8	192.5	TL	
710/55 - 34	STEEL BELTED	94069002	LS2	168 A2/163 A6	14	DW 24 B		27.6	64.6	29.8	192.5	TL	E11-106R-007156

Printed on 4/14/2024 3:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..